

**LOADING PORTS CHARACTERISTICS OF T.M.O.**

<i>MERSIN</i>	
<b>BERTH LENGTH</b>	490 m
<b>BERTH WIDTH</b>	-
<b>SEA WATER DRAFT</b>	13,20 m
<b>DAILY LOADING RATE IN BULK (MT/DAY)</b>	FOR THE VSL(S) WITH B/L QUANTITY
	WHEAT
	0 - 5.250 MT : 4.000 MT/DAY 5.251 - 10.500 MT : 4.000 MT/DAY 10.501 - 26.250 MT : 5.000 MT/DAY

**LOADING PORTS CHARACTERISTICS OF T.M.O.**

<i>ISKENDERUN</i>	
<b>BERTH LENGTH</b>	250 m
<b>BERTH WIDTH</b>	42 m
<b>SEA WATER DRAFT</b>	13,10 m
<b>LOADING BOOM HORIZONTAL</b>	Max: 48 m - Min: 12 m
<b>LOADING BOOM VERTICAL LENGTH</b>	Max: 43 m - Min: 10 m
<b>DAILY LOADING RATE IN BULK (MT/DAY)</b>	FOR THE VSL(S) WITH B/L QUANTITY
	WHEAT
	0 - 5.250 MT : 3.000 MT/DAY
	5.251 - 10.500 MT : 3.000 MT/DAY
	10.501 - 26.250 MT : 4.000 MT/DAY
	26.251 - 52.500 MT : 5.000 MT/DAY